



DIN 1587

HEXAGON DOMED CAP NUTS



Teknik Bilgiler / Technical Informations								
Thread size / Anma çapı (d)			M4	M5	M6	M8	M10	M12
Pitch / Diş adımı	P		0,70	0,80	1,00	1,25	1,50	1,75
Head width / Anahtar ağızı	s	min.	6,78	7,78	9,78	12,73	16,00	18,00
		max.	7,00	8,00	10	13	17	19
Diagonal / Köşegen	e	min.					17,77	20,03
		max.	7,66	8,79	11,05	14,38	18,90	21,10
Height / Yükseklik	h	min.	7,64	6,64	11,57	14,57	17,57	21,48
		max.	8,00	10,00	12,00	15,00	18,00	22,00
Diameter / Çap	d _k	min.					15,00	17,00
		max.	6,50	7,50	9,50	12,50	16,00	18,00
Weight / Ağırlık	gr/p		3,80	4,00	4,66	11,00	20,10	28,30

Thread size / Anma çapı (d)			M14	M16	M18	M20	M22	M24
Pitch / Diş adımı	P		2,00	2,00	2,50	2,50	2,50	3,00
Head width / Anahtar ağızı	s	min.	20,67	23,00	26,67	29,67	31,61	35,38
		max.	22,00	24,00	27,00	30,00	32,00	36,00
Diagonal / Köşegen	e	min.	23,35				35,72	
		max.	24,49	26,75	30,14	33,53	37,72	39,98
Height / Yükseklik	h	min.	24,48	27,48	31,38	33,38	38,38	41,38
		max.	25,00	28,00	32,00	34,00	39,00	42,00
Diameter / Çap	d _k	min.	20,00				31,00	
		max.	21,00	23,00	26,00	28,00	33,00	34,00
Weight / Ağırlık	gr/p		57,20	54,30	95,00	104	129	216

Thread size / Anma çapı (d)			5/32	3/16	1/4	5/16	3/8	1/2
Pitch / Diş adımı	P		32,00	24,00	20,00	18,00	16,00	13,00
Head width / Anahtar ağızı	s	min.	7,00	8,00	11,00	13,00	14,00	22,00
		max.						
Diagonal / Köşegen	e		7,90	9,65	12,40	14,15	15,95	21,34
Height / Yükseklik	h		8,00	10,00	12,00	15,00	14,47	25,00
Diameter / Çap	d _k		6,50	7,50	10,50	12,50	13,50	21,50
Weight / Ağırlık	gr/p		1,31	1,33	3,14	6,18	8,10	13,50

DIN 1587 hexagon domed cap nuts have a smooth rounded head that covers the hex nut base. The domed surface protects the bolt threads underneath while providing a finished appearance and may improve safety in certain circumstances.